

Palmer Stamping Facility—Progressive and Line die presses.

											COIL DATA*				
Press	Press			Shut	Stroke s /	BOLSTER		RAM			Thickn ess	Width			Weight
No.	Manufactur er	Tons	Stroke	Height	Minute	Width (F-B)	Length (L-R)	Width (F-B)	Length (L-R)	Adjustment	min. - max.	min.- max.	O.D.	I.D.	Max.
P-109	Bliss	400	16"	34"	10-40	48"	96"	48"	96"	10"	.030"- .250"	0 - 24"	60" MAX	20" - 24"	Use OD max
P-200	Verson	400	10"	34"	10-55	60"	96"	60"	96"	10"	.030"- .250"	0-38"	72" MAX	20" -24"	Use OD max
P-100	Bliss	150	4"	18"-20"	60	36"	59"	20"	44"	3.24"	.030- .250"	12" MAX	60" MAX	20"-24"	Use OD max
P-221	Bliss	150	4"	22"	35-105	36"	47"	20"	41"	1.5"	.025- .250"	12" MAX	60" MAX	20"-24"	Use OD max
P-102	Bliss	110	8	16"	60	27"	42"	21"	28"	4"	.025- .200"	18" MAX	50" MAX	20"-24"	Use OD max
P-105	Bliss	60	4"	6.5"- 10.5"	30-100	22"	32"	11"	17"	1.5"	.025- .100"	24" MAX	50" MAX	20"-24"	Use OD max
P-111	Bliss	35	3"	6.25"- 8.75"	S.S	18"	27"	9"	12"	2.5"	.025- .125	N/A	NA/ N/A	N/A	N/A
P-233	Bliss	150	11"	10"-18"	S.S.	36"	42"	20"	32	4"	.025- .375"	N/A	N/A	N/A	N/A
P-250	DELTA MFG – DRILL PRESS TAPPER														
P-251	SNOW AIR TOOL – TAPPING MACHINE														
P-224	ALMCO – VIBRATOR PARTS DEBURRING AND CLEANING MACHINE									18" LONG X 3" DEEP X 3" HIGH					